

TECHNISPRAY PAINTS LTD.

Linton House, Catherine Street, Aston, Birmingham B6 5RS U.K.

Tel: ++44 (0) 121 326 8020 Fax: ++44 (0) 121 327 1507

Email: enquiries@kolorbond.co.uk

www: kolorbond.co.uk

Polyprep

Polyprep is an adhesion promoter for use on polypropylene when spraying with Kolorbond paint.

The polypropylene substrate should be cleaned then sprayed with a mist coat of Polyprep. As soon as the Polyprep has flashed off the polypropylene can be sprayed with Kolorbond in the normal way

It is always worth checking small items, believed to be PVCu, for adhesion before spraying. If the adhesion of Kolorbond is poor, the items may be made from polypropylene or mixed plastics. If so, use Polyprep as stated above.

SCROLL DOWN FOR MSDS



TECHNISPRAY PAINTS LTD.

Linton House, Catherine Street, Aston, Birmingham B6 5RS U.K.

Tel: ++44 (0) 121 326 8020 Fax: ++44 (0) 121 327 1507

Email: enquiries@kolorbond.co.uk

www: kolorbond.co.uk

SAFETY DATA SHEET - REGULATIONS 1994 (CHIP 2)

Technispray Paints Limited urges the customer receiving this Material Safety Data Sheet to study it carefully to become aware of hazards, if any, of the product involved.

In the interests of safety you should:

- 1) notify your employees, agents and contractors of the information on this sheet,
- 2) furnish a copy to each of your customers for the product, and
- 3) request your customers to inform their employees and customers as well.

1) Identification and Company

Date revised: 03 02 14

Revision No:16

Company:

TECHNISPRAY PAINTS LIMITED

Product Name:

POLYPREP

Chemical Characterisation:

Solvent

Form

Liquid - 1 litre, 5 litre cans

Colour

none

Odour

Characteristic odour

2) Composition

| Material | CAS No: % (weight) | EINECS no. | Symbol | Risk Phrases |
|----------------------|-----------------------|------------|-----------|-----------------|
| Toluene | 108-88-3 20-30 | 203-625-9 | F, Xn,Xi | 11-38-48-67 |
| 4-Methylpentan-2-one | 108-10-1 60-70 | 203-550-1 | F, Xn, Xi | 11,20,36/37, 66 |
| Chlorobenzene | 108-90-7 0-0.5 | 203-628-5 | Xn, N | 10, 20,51/53 |
| Ethylbenzene | 100-41-4 0-0.5 | 202-849-4 | F, Xn | 10, 20 |
| Xylene | 1330-20-7 | 215-535-7 | Xn, Xi | 10, 20/21, 38 |

The texts of the R phrases are listed in 15)

3) Hazards Identification

Physical

Highly flammable. Harmful

Adverse Human Effects

Can enter the body by inhalation, ingestion, or through the skin. Irritates the eyes, skin and respiratory tract. Liquid removes the skin's natural oils. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

in accordance with EU Directives

4) First Aid Measures

| | |
|------------|---|
| Inhalation | Move the exposed person to fresh air at once. Get medical attention immediately. For breathing difficulties oxygen may be necessary. If rapid recovery does not follow, apply artificial respiration. |
| Ingestion | Do not induce vomiting. Obtain medical attention immediately. |
| Skin | Wash the skin immediately with soap and water. Use a moisturiser. |
| Eye | Get medical attention if any discomfort continues. Flush with plenty of water for several minutes. Make sure to remove any contact lenses before rinsing. Continue to rinse for at least 15 minutes. If irritation persists, refer for medical attention. |

5) Fire Fighting Measures

| | |
|----------------------------------|---|
| Extinguishing Media | Use a dry chemical powder, foam or carbon dioxide extinguisher, sand or earth. Do not use water in a jet. |
| Special Fire Fighting Procedures | Containers close to fire should be removed or cooled with water. Use water to keep fire-exposed containers cool. |
| Unusual Fire & Explosion Hazards | Risk of explosion if heated. |

6) Accidental Release Measures

| | |
|------------------------------|--|
| Spillage/Leakage/Gas Leakage | Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Wear the necessary protective equipment. Prevent the liquid from spreading with sand or sawdust. Shovel up and remove to a safe place. Flush contaminated area with water. If leakage cannot be stopped evacuate area. Ventilate well. Do not contaminate water sources or sewer. Shovel up and remove to a safe place. Extinguish naked flames. Ensure adequate ventilation. Wear protective clothing and breathing apparatus as outlined below. |
|------------------------------|--|

7) Handling and Storage

| | |
|----------------------|--|
| Handling Precautions | Ensure adequate positive ventilation to keep concentrations well below hazard levels. Keep away from heat, sparks and open flames. |
| Storage Precautions | Containers must not be exposed to direct sunlight or temperatures above 50°C. Store away from oxidising agents. Avoid exposure to sources of heat or ignition. Keep containers tightly closed. Avoid build up of static electricity. |

in accordance with EU Directives

8) Exposure Controls and Personal Protection

| Name | CAS No. | STD | LT EXP (8 hrs) | ST EXP (15 min) |
|----------------------|-----------|-----|----------------|-----------------|
| Toluene | 108-88-3 | OES | 50 ppm | 100 ppm |
| 4-Methylpentan-2-one | 108-10-1 | OES | 50 ppm | 100 ppm |
| Chlorobenzene | 108-90-7 | OES | 1 ppm | 3 ppm |
| Ethylbenzene | 100-41-4 | OES | 100 ppm | 125 ppm |
| Xylene | 1330-20-7 | OES | 50ppm | 100 ppm |

OES = Occupational Exposure Standard

SUP = Supplier's Recommendation

SK = Can be absorbed through skin

| | |
|---------------------------------|---|
| Protective Equipment | Wear goggles giving complete protection to eyes. Wear nitrile rubber gloves. Wear overalls. Avoid contact with liquid. Wear an approved breathing apparatus when concentrations above 100 ppm are present. |
| Ventilation | Provide adequate general and local exhaust ventilation. |
| Respirators | No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL). |
| Protective Gloves | Use protective nitrile rubber gloves. |
| Eye Protection | Use approved safety goggles or face shield. |
| Protective Clothing | Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. |
| Industrial Hygiene Work Routine | DO NOT SMOKE IN WORK AREA. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material. |

9) Physical and Chemical Properties

| | |
|--------------------------|---|
| Appearance | Liquid - various size containers. |
| Odour | Aromatic |
| Colour | Colourless |
| Change in Physical State | Melting point below : n.d.a Boiling point : n.d.a. |
| Density | 0.83 g/cm ³ |
| Solubility in water | immiscible |
| pH Value | (20°C) not applicable |
| Flash Point | 4°C |
| VOC | 0.780 Kgs/Lt |

in accordance with EU Directives

10) Stability and Reactivity

| | |
|----------------------------------|---|
| Thermal Decomposition | Thermal decomposition will occur. |
| Hazardous Decomposition Products | Fire creates: Vapours / Gases / Carbon Monoxide (CO) & Carbon dioxide (CO ₂) Fumes |
| Hazardous Reactions | No hazardous decomposition products when stored and used correctly. |
| Conditions To Avoid | Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents, strong alkali, and strong mineral acids. |

11) Toxicological Information

| | |
|-------------------------|---|
| Health Hazards, General | Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. |
| Inhalation | Gas or vapour in high concentrations may irritate respiratory system. Gas or vapour displaces oxygen available for breathing (asphyxiant). |
| Skin | Product has a de-fatting effect on the skin. Prolonged or repeated exposure may cause severe irritation. |
| Eyes | Irritating to the eyes. Spray and vapour in the eyes may cause irritation and smarting. May cause severe irritation to eyes. |
| Route of entry | Inhalation. Skin and /or eye contact. |

12) Ecological Information

Do not allow escape into water, wastewater drains or soil.

13) Disposal Considerations

Empty containers must not be burned because of explosion hazard.
Dispose of in accordance with the Local Authority requirements.
Contact specialist disposal companies.

in accordance with EU Directives

14) Transport Information

LITRES:

ADR:

| | |
|-----------------------------------|-------|
| ADR: UN Number | 1263 |
| ADR: Proper Shipping Name | Paint |
| ADR: Class | 3 |
| ADR: Packing Group | II |
| ADR: Classification Code | F1 |
| ADR: Transport Category | 2 |
| ADR: Hazard Identification Number | 33 |

Shipping:

| | |
|----------------------------|----------|
| IMDG: UN Number | 1263 |
| IMDG: Proper Shipping Name | Paint |
| IMDG: Class | 3 |
| IMDG: Packing Group | II |
| IMDG: EmS | F-E, S-E |

Air Transport:

| | |
|----------------------------|-------|
| IATA: UN Number | 1263 |
| IATA: Proper Shipping Name | Paint |
| IATA: Class | 3 |
| IATA: Packing Group | II |
| IATA: Packing Instruction | 305 |

15) Regulatory Information

Risk Phrases

| | |
|---------|---|
| R-10 | Flammable |
| R-11 | Highly flammable |
| R-20 | Harmful by inhalation. |
| R-36 | Irritating to eyes. |
| R-36/37 | Irritating to eyes and respiratory system |
| R-37/38 | Irritating to respiratory system and skin. |
| R-43 | May cause sensitisation by skin contact. |
| R50/53 | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment |
| R52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment |
| R-66 | Repeated exposure may cause skin dryness or cracking. |
| R-67 | Vapours may cause drowsiness and dizziness. |

Safety Phrases

| | |
|------|---|
| S-2 | Keep out of reach of children. |
| S-16 | Keep away from heat and sources of ignition. |
| S-21 | No Smoking. |
| S-23 | Do not breathe vapour/spray. |
| S-24 | Avoid contact with skin. |
| S-25 | Avoid contact with eyes. |
| S-26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S-37 | Wear suitable gloves. |
| S-51 | Use only in well ventilated areas. |

in accordance with EU Directives

