

TECHNISPRAY PAINTS LTD.

Linton House, Catherine Street, Aston, Birmingham B6 5RS U.K.

Tel: ++44 (0) 121 326 8020 Fax: ++44 (0) 121 327 1507

Email: enquiries@kolorbond.co.uk

www: kolorbond.co.uk

Vinylprep

Vinylprep is a solvent based cleaner for use on soft vinyl before spraying with Vinylkote.

Vinylprep removes contaminants including polishes and lacquers

The substrate should be cleaned using Vinylprep on a clean white cloth. As you clean, the cloth should be turned so that a clean area of the cloth is always being used.

The vinyl may feel a little tacky after cleaning with Vinylprep. This will help with the adhesion of the paint.

You must always wear gloves when using this product. **Take care;** Vinylprep will damage other paintwork and the finish to soft vinyl which you do not intend to paint.

Used cleaning cloths must be disposed of in a metal container. The residual Vinylprep is flammable and friction from cleaning process can build up static electricity. A static spark can cause ignition of the cloth.

SCROLL DOWN FOR MSDS



TECHNISPRAY PAINTS LTD.

Linton House, Catherine Street, Aston, Birmingham B6 5RS U.K.

Tel: ++44 (0) 121 326 8020 Fax: ++44 (0) 121 327 1507

Email: enquiries@kolorbond.co.uk

www: kolorbond.co.uk

SAFETY DATA SHEET - REGULATIONS 1994 (CHIP 2)

KOLOR COATINGS LIMITED urges the customer receiving this Material Safety Data Sheet to study it carefully to become aware of hazards, if any, of the product involved.

In the interests of safety you should:

- 1) notify your employees, agents and contractors of the information on this sheet,
- 2) furnish a copy to each of your customers for the product, and
- 3) request your customers to inform their employees and customers as well.

1) Identification and Company

Date revised: 03 02 14

Revision No:10

Company:

Technispray Paints Ltd.

Product Name:

Vinylprep

Chemical Characterisation:

Solvent-based cleaner for use with Vinylkote

Form

Liquid - 1 litre, 5 litre

Colour

Clear

Odour

Characteristic

2) Composition

Material	CAS No:	% Content Risk	Symbol	Risk Phrases
Methyl Isobutyl Ketone	108-10-1	70 - 90	Xi	11,20,36,37,66
Xylene	1330-20-7	10 - 30	Xn	11,20

3) Hazards Identification

Physical

Highly Flammable. R-11

Adverse Human Effects
the skin.

Can enter the body by inhalation, ingestion, or through

Irritates the eyes, skin and respiratory tract.

Liquid removes the skin's natural oils.

Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

in accordance with EU Directives

4) First Aid Measures

Inhalation	Move the exposed person to fresh air at once. Get medical attention immediately. For breathing difficulties oxygen may be necessary. If rapid recovery does not follow, apply artificial respiration.
Ingestion	Do not induce vomiting. Obtain medical attention immediately.
Skin	Wash the skin immediately with soap and water. Use a moisturiser. Get medical attention if any discomfort continues.
Eye	Flush with plenty of water for several minutes. Make sure to remove any contact lenses before rinsing. Continue to rinse for at least 15 minutes. If irritation persists, refer for medical attention.

5) Fire Fighting Measures

Extinguishing Media	Use a dry chemical powder, foam or carbon dioxide extinguisher, sand or earth. Do not use water in a jet.
Special Fire Fighting Procedures	Containers close to fire should be removed or cooled with water. Use water to keep fire-exposed containers cool. Wear self-contained breathing apparatus and suitable protective clothing.
Unusual Fire & Explosion Hazards	Risk of explosion if heated.

6) Accidental Release Measures

Spillage/Leakage/Gas Leakage	Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Wear the necessary protective equipment. Prevent the liquid from spreading with sand or sawdust. Shovel up and remove to a safe place. Flush contaminated area with water. If leakage cannot be stopped evacuate area. Ventilate well. Do not contaminate water sources or sewer. Shovel up and remove to a safe place. Extinguish naked flames. Ensure adequate ventilation. Wear protective clothing and breathing apparatus as outlined below.
------------------------------	--

in accordance with EU Directives

7) Handling and Storage

Handling Precautions	Ensure adequate positive ventilation to keep concentrations well below hazard levels. Keep away from heat, sparks and open flames.
Storage Precautions	Containers must not be exposed to direct sunlight or temperatures above 50°C. Store away from oxidising agents. Avoid exposure to sources of heat or ignition. Keep containers tightly closed. Avoid build up of static electricity.

8) Exposure Controls and Personal Protection

Name	CAS No.	STD	LT EXP (8 hrs)	ST EXP (15 min)
Methyl Isobutyl Ketone	108-10-1	OES	50 ppm (SK)	100 ppm(SK)
Zylene	1330- 20-7	OES	50 ppm(SK)	150 ppm(SK)

Comments OES = Occupational Exposure Standard
SUP = Supplier's Recommendation
SK = Can be absorbed through skin

Protective Equipment	Wear goggles giving complete protection to eyes. Wear nitrile rubber gloves. Wear overalls. Avoid contact with liquid. Wear an approved breathing apparatus when concentrations above 100 ppm are present.
Ventilation	Provide adequate general and local exhaust ventilation.
Respirators	No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).
Protective Gloves	Use protective nitrile rubber gloves.
Eye Protection	Use approved safety goggles or face shield.
Clothing Protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Industrial Hygiene Work Routine	DO NOT SMOKE IN WORK AREA. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.
	No eating or drinking while working with this material.

in accordance with EU Directives

9) Physical and Chemical Properties

Appearance	Liquid
Odour	Characteristic
Colour	Clear
Melting point	- 60°C
Boiling point	115 - 120 °C
Density	0.85 g/ml @ 20 °C
Solubility in water	(20°C) less than 20 g/l
Flash Point	13 °C Closed Cup
Ignition Temperature	>450°C
Flammability Limit (upper %)	9.75
Flammability Limit (lower %)	1.55

10) Stability and Reactivity

Thermal Decomposition	Thermal decomposition will occur.
Hazardous Decomposition Products	Fire creates: Vapours / Gases / Carbon monoxide (CO) & Carbon dioxide (CO ₂) Fumes
Hazardous Reactions	No hazardous decomposition products when stored and used correctly.
Conditions to Avoid	Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents, strong alkali, and strong mineral acids.

11) Toxicological Information

Health Hazards, General	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Gas or vapour I high concentrations may irritate respiratory system. Gas or vapour displaces oxygen available for breathing (asphyndent).
Skin	Product has a de-fatting effect on the skin. Prolonged or repeated exposure may cause severe irritation.
Eyes	Irritating to the eyes. Spray and vapour in the eyes may cause irritation and smarting. May cause severe irritation to eyes.
Route of entry	Inhalation. Skin and /or eye contact.

12) Ecological Information

Mobility	Rapidly volatilise and enter the atmosphere from both water and soil.
Degradability	Biologically degradable.
Bioaccumulative Potential	Slight potential to bioaccumulate.
Aquatic Toxicity	LC50 96hr (fish) - 505 mg/l EC50 24 hr (daphnia) - 3682 mg/l

Do not allow to escape into water, wastewater drains or soil.

in accordance with EU Directives

13) Disposal Considerations

Empty containers must not be burned because of explosion hazard.
Dispose of in accordance with the Local Authority requirements.
Contact specialist disposal companies.

14) Transport Information

LITRES:

ADR:

ADR: UN Number	1263
ADR: Proper Shipping Name	Paint Related Material
ADR: Class	3
ADR: Packing Group	II
ADR: Classification Code	F1
ADR: Transport Category	2
ADR: Hazard Identification Number	33

Shipping:

IMDG: UN Number	1263
IMDG: Proper Shipping Name	Paint Related Material
IMDG: Class	3
IMDG: Packing Group	II
IMDG: EmS	F-E, S-E

Air Transport:

IATA: UN Number	1263
IATA: Proper Shipping Name	Paint Related Material
IATA: Class	3
IATA: Packing Group	II
IATA: Packing Instruction	305

15) Regulatory Information

Risk Phrases	R-11	Highly Flammable.
	R-20	Harmful by inhalation.
	R-36	Irritating to eyes.
	R-37	Irritating to respiratory system.
	R-66	Repeated exposure may cause skin dryness or cracking.
Safety Phrases	S-9	Keep container in a well-ventilated place.

ignition.	S-16	Keep away from heat and sources of No Smoking.
	S-21	When using do not smoke.
	S-24	Avoid contact with skin.
	S-25	Avoid contact with eyes.
	S-29	Do not empty into drains.
	S-33	Take precautionary measures against static discharges.
	S-36	Wear suitable protective clothing.
	S-37	Wear suitable gloves.
	S-51	Use only in well-ventilated areas.

in accordance with EU Directives

UK Regulatory References: Supply)	Chemicals (Hazard Information and Packaging for Regulations 1994 (CHIP 2)
Supply)	Chemicals (Hazard Information and Packaging for Regulations 1994 (CHIP 2) Regulation 6
Supply)	Chemicals (Hazard Information and Packaging for (Amendment) Regulations 1996 (CHIP 96)
Supply)	Chemicals (Hazard Information and Packaging for (Amendment) Regulations 1997 (CHIP 97)
Supply)	Chemicals (Hazard Information and Packaging for (Amendment) Regulations 1998 (CHIP 98)
Supply)	Chemicals (Hazard Information and Packaging for (Amendment) Regulations 1999 (CHIP 99)
Supply)	Chemicals (Hazard Information and Packaging for (Amendment) (No. 2) Regulations 1999 (CHIP 99(2)) IATA - Dangerous Goods Regulations IMDG - International Maritime Dangerous Goods Code
UK Publication References: Dangerous for Supply.	ADR - Dangerous Goods Code Approved Guide to the Classification and Labelling of Substances and Preparations (Guidance on Regulations) (Fourth Edition) Safety Data Sheets for Substances and Preparations for Supply. (Approved Code of Practice)
Dangerous (Second Edition)	Approved Supply List - Information Approved for the Classification and Labelling of Substances and Preparations Dangerous for Supply. (Fifth Edition)

UK Environmental References:	Carriage of Dangerous Goods - Guidance for Consignors of Dangerous Goods.
UK Statutory References:	Occupational Exposure Limits.
	Control of Pollution (Special Waste Regulations) Act
	Rivers (Prevention of Pollution) Act
	Chemicals (Hazard Information and Packaging for Supply)
	Regulations 1994 (CHIP 2)

16) Other Information

Emergency Action	Notify Police and Fire Brigade immediately.
------------------	---

17) Disclaimer

Disclaimer	The information accumulated herein is believed to be accurate and reliable as of the date above, however Technispray Paints Ltd. makes no representation, warranty or guarantee nor assumes any legal responsibility as to its accuracy, reliability or completeness. Ultimate determination of suitability for intended use is the responsibility of the user.
------------	---

03 02 14 Rev. 10

in accordance with EU Directives