

TECHNISPRAY PAINTSLTD.

Linton House, Catherine Street, Aston, Birmingham B6 5RS U.K.

Tel: +44 (0)121 326 8020 Fax: +44 (0)121 327 1507

email: info@kolorbond.co.uk

www.kolorbond.co.uk



Application instructions for KolorKlad Paint



KolorKlad is suitable for coating most types of industrial cladding

N.B. This paint is for professional use only

1. Mask the substrate, covering all surfaces which do not require painting.
2. Clean the substrate using **Vinylkleen**. This will remove all water soluble contaminants together with most oils.
3. Thoroughly clean the surface again using **Windowprep** on a clean white cloth which should be regularly turned.
4. Lightly abrade the surfaces to be painted with red Scotchbrite and remove debris. Uncoated metals must be abraded with a grit paper to remove any oxidation
5. Check that the paint colour and gloss level are correct.
6. Thoroughly stir the **KolorKlad** paint making sure that any colourants on the base of the can are thoroughly mixed in.
7. Stir in **Thinners** to your individual requirements
8. Use a tack rag, if necessary, to remove any dust or swarf remaining on the surface of the substrate.
9. The sprayer must use a mask suitable for solvent paint. Skin must be protected by the use of gloves etc.
10. Spray the substrate with a light coat followed by a medium coat after 2 minutes flash off. If a further coat is required allow flash off between coats.
11. The paint will cure and harden overnight.